Α	В
1	Federal Transit Administration
2	Noise Impact Assessment Spreadsheet
3	Copyright 2007 HMMH Inc.
4	
5	
6	
7	DESCRIPTION OF THE FTA NOISE IMPACT ASSESSMENT SPREADSHEET
8	
9	This spreadsheet enables the user to predict noise levels from transit sources and evaluate the level of impact on noise-sensitive receivers. It incorporates the procedures for a General Noise Assessment contained in Chapter 5 of the Federal Transit Administration's guidance manual, "Transit Noise and Vibration Impact Assessment." The FTA guidance describes situations where a General Noise Assessment is appropriate. In situations where Detailed Noise Analysis is needed (e.g., for new fixed-guideway projects in preliminary engineering), this spreadsheet should not be used; instead, the procedures in Chapter 6 of the guidance should be followed.
10	January and Programme Control of the
11	The main spreadsheet is divided into three sections: Receiver Parameters, Noise Source Parameters, and Project Results. The sections below give directions on how the user provides the relevant inputs to the model to obtain project noise levels and an assessment of impact on selected receivers. The default spreadsheet is set up to model the transit scenario in Example 5-1, Part 1 in the guidance manual. The user is encouraged to use the spreadsheet to complete the other examples in Chapter 5 to understand how the spreadsheet works. References to the FTA guidance are made below where elaboration is needed.
12	
13	Receiver Parameters:
14	
15	A "receiver" is a noise-sensitive site. The user begins by entering information about the receiver in the green-shaded cells. The Receiver cell is for the user's own reference and can be any identifier.
16	Collective Collection of the door of own forestine and oath be any facilities.
17 18	Land Use Category: With respect to each receiver, the user must first select the appropriate land-use category from three choices provided in a drop-down list. The choice of land-use category determines the specific noise descriptor and impact criteria that will be used in the spreadsheet calculations. FTA's noise impact criteria are based on Ldn for Category 2 land uses and one-hour Leq for the noisiest hour of transit-related activity for Category 1 and 3 land uses (see Table 3-2 in the guidance).


A	В
19	Existing Noise: The user must enter the existing noise level at the receiver. The validity of the noise impact assessment depends heavily on an accurate estimate of existing noise. Full or partial measurements are always preferred. Depending on the land-use category selected, the user enters the measured existing noise level (Ldn or Leq(h)) in the cell, Existing Noise (Measured or Generic Value). For situations where actual measurements cannot be obtained, the user should apply the appropriate noise levels from Table 5-7 in the guidance manual. The generic noise environments in Fig. 2-17 could be used but only if the impact assessment is in terms of Ldn. Further information on determining existing noise levels – including a discussion of the methods considered most accurate — is found in Appendix D in the manual.
20	Noise Source Parameters:
22	Noise Source Parameters.
23	The user enters information about the noise source or sources in the blue-shaded cells.
24	The user enters information about the noise source of sources in the blue-shaded cells.
25	Number of Noise Sources: First, the number of noise sources to be analyzed for a given receiver must be entered. From the drop-down list, the user can specify up to six separate sources. The spreadsheet will then calculate a combined noise level (Ldn or Leq(h) depending on receiver land use) from all noise sources at the receiver. For instance, when determining noise impact at a receiver located near a commuter rail track, two sources can be selected to calculate noise levels from a train which is made up of a diesel-electric locomotive and rail cars. Multiple sources can also be used to determine combined noise from a complex situation, such as a light rail transit station where the model can calculate the total noise from LRT trains, grade-crossing bells, and park-and-ride activity.
26	
27 28	Noise Source Parameters: The number of noise sources specified by the user determines the number of Noise Source Parameters boxes displayed by the spreadsheet for which project data must be entered. For each box, the user must first specify a Source Type, either Fixed Guideway, Highway/Transit, or Stationary Source. Selecting a source type leads to a drop-down list in the cell below from which the user chooses a specific source. For example, selecting Fixed Guideway leads to a list of specific sources including diesel-electric locomotives, DMUs, etc.

	Α	В
29		Specific Source: Depending on the specific source selected, the subsequent cells in the box ask the user to provide operating information for the project, such as frequency of operations, duration of individual events, average speed, etc. The specific operating information needed depends on the source and also the land-use category that was selected under Receiver Parameters. If land-use category 2 was selected, operating data for daytime (7 am-10 pm) and nighttime (10 pm-7 am) hours must be provided. If category 1 or 3 was selected, operating data for the busiest transit hour during the time of use of the noise-sensitive facility must be provided. Parameters for all land-use categories are based on hourly or average hourly traffic, and number of locomotives/rail cars/rail transit vehicles in a given consist. The specific parameters will change based on the specific source. Refer to tables 5-2, 5-4, and 5-6 for further definition of the parameters and options.
30		
31		<u>Please note:</u> After the operating data are entered in the cells for a specific source, if the user should subsequently change the specific source, the previously entered operating data will not be wiped out. The user must enter the new operating data for the new source over the old data in the cells.
32		
33 34		Distance: The distance from the source to the receiver must be specified. If more than one source is being analyzed, the distances between the sources and the receiver may be different. In the case of a commuter train, however, the distance between the two sources (locomotive and rail cars) and the receiver would be the same.
35	A	djustments: Various adjustments are available depending on the specific source chosen above:
36		
		Noise Barrier: This allows the user to approximate the benefits of installing a noise barrier. If "Yes" is selected
37		from the drop-down list, the noise level for the source is reduced by 5 dB for Rail Transit Vehicles, Rail Cars, Highway/Transit sources, and Stationary sources. This is appropriate only if the following conditions are met: the noise barrier needs to be high enough to completely block the line-of-sight between the noise source and the receiver; the barrier must be free of any gaps or openings; and the barrier should be constructed out of an outdoor weather-resistant material such as wood or concrete. If these conditions are not met, the effectiveness of the barrier will be overestimated. If the user is not sure these conditions can be met, then "No" should be chosen. Refer to Section 6.8.3 in the guidance for more information.
37 38		Highway/Transit sources, and Stationary sources. This is appropriate only if the following conditions are met: the noise barrier needs to be high enough to completely block the line-of-sight between the noise source and the receiver; the barrier must be free of any gaps or openings; and the barrier should be constructed out of an outdoor weather-resistant material such as wood or concrete. If these conditions are not met, the effectiveness of the barrier will be overestimated. If the user is not sure these conditions can be met, then "No" should be chosen.
38		Highway/Transit sources, and Stationary sources. This is appropriate only if the following conditions are met: the noise barrier needs to be high enough to completely block the line-of-sight between the noise source and the receiver; the barrier must be free of any gaps or openings; and the barrier should be constructed out of an outdoor weather-resistant material such as wood or concrete. If these conditions are not met, the effectiveness of the barrier will be overestimated. If the user is not sure these conditions can be met, then "No" should be chosen. Refer to Section 6.8.3 in the guidance for more information. Jointed Track/Embedded Track/Aerial Structure: These adjustments are for Rail Transit Vehicles and Rail Cars only. If "Yes" is selected from the drop-down list for any of these sources, the noise level of the source is
		Highway/Transit sources, and Stationary sources. This is appropriate only if the following conditions are met: the noise barrier needs to be high enough to completely block the line-of-sight between the noise source and the receiver; the barrier must be free of any gaps or openings; and the barrier should be constructed out of an outdoor weather-resistant material such as wood or concrete. If these conditions are not met, the effectiveness of the barrier will be overestimated. If the user is not sure these conditions can be met, then "No" should be chosen. Refer to Section 6.8.3 in the guidance for more information. Jointed Track/Embedded Track/Aerial Structure: These adjustments are for Rail Transit Vehicles and Rail

	Α	В
42		Project Results:
43		
44 45		Results are given in the red boxes to the right of Receiver Parameters and Noise Source Parameters. In addition to a summary box, separate boxes below display the noise prediction results for each source analyzed.
46 47		Project Results Summary: This box shows the total project noise level at the receiver (Ldn or Leq(h)) which is the combined noise level from all the sources analyzed. The Total Noise Exposure shows the new cumulative noise level when project noise is added to the existing noise level. The Increase shows the difference between the existing and the new cumulative noise environments. This box also predicts the level of impact ("None," "Moderate," or "Severe") based on FTA's noise impact criteria (refer to Fig. 3-1 in the guidance manual).
48		Distance to Impact Contours: In certain cases the spreadsheet will indicate the distances from the noise source to the points at which moderate impact and severe impact occur. This can only be done when one or two sources are being analyzed. With two sources, both must be the same source type and the same distance from the receiver, for example, a commuter train with a locomotive and rail cars. Example 5-1, Part 1 in the guidance manual is such a case. Distance to impact contours will not be shown for more complex cases.
49		
50		Impact Plots:
51		
52 53		Noise Impact Criteria: The level of impact is determined based on the combined noise level from all sources at the receiver and the existing noise level at the receiver. The level of impact is plotted against the noise impact criteria curves from Figure 3-1 in the guidance. This is displayed in the Calculations tab as well as the Impact Plots tab. The Moderate and Severe impact criteria curves are based on the land-use category chosen in the Receiver Parameters box. Therefore, the impact criteria curves and the y-axis (Project Noise Level) label will conform automatically to the land-use category selected.
-		
54		Increase in Cumulative Noise Levels Allowed: In certain cases, the cumulative form of the noise impact criteria should be used. In general, these situations occur when the existing noise environment already has transit noise in it and the existing noise sources may change as a result of the project. This plot from Figure 3-2 in the guidance presents noise impact in terms of the increase in cumulative noise levels due to the project. See sections 3.1.2 and 3.2.3 for further discussion on when this form of the criteria should be used. In both plots, the Project Noise Level/Increase in Cumulative Noise Level values are shown next to the marker.
55		

	Α	В
56		
57		Report:
58		
59		The report page tabulates the noise levels for each source as well as the total combined noise level for all sources.
60		
61		 First two columns list the sources and their distances from the receiver.
62		Third column shows the noise from each source.
63		Fourth column has the existing noise level at the receiver.
64		 Fifth and sixth columns give the noise impact criterion levels, Moderate and Severe, that relate to the existing ambient noise level in the fourth column.
65		 Seventh column gives the noise impact rating for each source. (This information may be useful in identifying which source is dominant in causing impact.)
66		 Bottom row of the table shows the cumulative noise effect of all sources and the resulting overall impact at the receiver.
67		
68		This table can be copied and pasted into a word-processing or spreadsheet document to perform additional calculations or to present results for publication.
69		
70		Finally, the steps outlined above would be repeated for each individual receiver and receiver representing a cluster of noise-sensitive sites that may be affected by the project. The boundaries for the noise impact assessment can be established by using the screening procedure in Chapter 4 of the guidance.

Α	В	С	D	E	F	G	Н
1	Federal Transit Adm	ninistration					
2	Noise Impact Assess	sment Spreadsheet					
3	Copyright 2007 HMM	/IH Inc.					
4	June 8, 2007						
5							
6		Project:	FTA Example 5-1, Part 1				
7						Project Results Summary	
3						Existing Ldn:	60 dBA
)						Total Project Ldn:	
0	Receiver Parameters	S				Total Noise Exposure:	
1		Receiver:	Receiver 1			Increase:	6 dB
2		Land Use Category:	2. Residential			Impact?:	Severe
3	Existir	ng Noise (Measured or Generic Value):	60 dBA				
4						Distance to Impact Contours	
5						Dist to Mod. Impact Contour:	
6						Dist to Sev. Impact Contour:	
7	Noise Source Param	eters					
8		Number of Noise Sources:	4				
9							
0	Noise Source Param	eters	Source 1				
1		Source Type:	Fixed Guideway				
2		Specific Source:	Diesel Electric Locomotive			Source 1 Results	
3	Daytime hrs	Avg. Number of Locos/train	1			Leq(day):	61.8 dBA
4		Speed (mph)	40			Leq(night):	
5		Avg. Number of Events/hr	2.8				63.8 dBA
6							
7	Nighttime hrs	Avg. Number of Locos/train	1				
8		Speed (mph)	40				
9		Avg. Number of Events/hr	0.7			V	
0		<u> </u>					
1	Distance	From Source to Receiver (ft)	50				
2	Adjustments						
3						Y	
4							
5							
6							
7	Noise Source Param	eters	Source 2				



	U	٧	W	Ιx	ΥZ	AA	AB	AC	AD	AE
1										
2										
3										
4										
4 5										
6										
7										
8										
9										
10 11										
12										+
12										
13										
14										
15 16 17										
16										
17							1			
18										
18 19 20										
20						_ =				
21						372	3			
22										
23										
24										
25										
23 24 25 26 27										
27										
28 29 30 31										
29		1 1								
30										
31										
32										
33 34 35										
34							1			
35										
36										
37										

	AF	AG	AH	AI	AJ	AK	AL	AM	AN
1	The state of the s	1 2 2 2							
2									
3									
4									
4 5									
6									
7									
8									
8 9									
10									
11									
12									
11 12 13									
14									
15									
15 16									
17									
17 18 19									
19									
20									
21									
22									
23									
24									
25									
26									
20 21 22 23 24 25 26 27									
28 29 30 31									
30									
31									
32									
33									
34									
35									
32 33 34 35 36 37									
37									

	AO	AP	AQ	AR	AS	AT	AU	AV	AW	AX	AY	AZ
1												
2												
3												
4												
5												
6												
7												
8												
9							1 1		1			
10												
11 12												
12												
13												
14							[1			
15												
16												
15 16 17 18 19												
18												
19												
20												
21												
22												
20 21 22 23 24 25 26 27												
24	7.1											
25							7					
26												
27												
							(=					
29							1					
30												
31												
28 29 30 31 32 33 34 35 36 37												
33												
34									1			
35									1 = 0			
36												
37												

	BA
1	DA
2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
12	
13	
14	
15	
16	
17	
18	
19	
20	
21 22	
22	
23	
24	
25	
26	
27	
28	
29	
30	
31	
32	
33 34	
35	
36	
37	

Α	В	С	D	E	F	G	Н
38		Source Type:	Fixed Guideway				
39		Specific Source:	Rail Car			Source 2 Results	
40	Daytime hrs	Avg. Number of Rail Cars/train	3			Leq(day):	53.7 dBA
41		Speed (mph)	40			Leq(night):	47.7 dBA
42		Avg. Number of Events/hr	2.8				55.6 dBA
43						Incremental Ldn (Src 1-2):	64.4 dBA
44	Nighttime hrs	Avg. Number of Rail Cars/train	3				
45		Speed (mph)	40				
46		Avg. Number of Events/hr	0.7				
47							
48	Distance	From Source to Receiver (ft)	50				
49	Adjustments	Noise Barrier?	No				
50		Jointed Track?	No				
51		Embedded Track?	No				
52		Aerial Structure?	No				
53							
54	Noise Source Paran	neters	Source 3				
55		Source Type:	Stationary Source				
56		Specific Source:	Layover Tracks (commuter rail)			Source 3 Results	
57	Daytime hrs	Avg. Number of Trains/hr				Leq(day):	0.0 dBA
58	,	9				Leq(night):	
59							6.4 dBA
50						Incremental Ldn (Src 1-3):	64.4 dBA
61	Nighttime hrs	Avg. Number of Trains/hr					
52		, (1 g) 11 ann 2 (1) 1 (1)					
63							
54							
65	Distance	From Source to Receiver (ft)					
66	Adjustments	Noise Barrier?	No				
57							
58							
69							
70							
71	Noise Source Paran	neters	Source 4				
72		Source Type:	Fixed Guideway				
73		Specific Source:	Diesel Electric Locomotive			Source 4 Results	
	Daytime hrs	Avg. Number of Locos/train				Leq(day):	0 0 dBA
75	Day anne ma	Speed (mph)				Leq(day).	

	I	J	KL	M	N	0	Р	Q	R	S	Т
38	S.										
39	od		♦ 6 dB								
40	— <u>û</u> 3				_						
41	Noise Exposu				_						
42	— ž ₀ [_						
43	40 45	50 55	60 65	70 75	80 -						
	-	Existing N	oise Exposure (d	IBA)	_						
44 45	-				-						
46	Mod	lerate Impact	Severe Impac	ct • Rec	eiver 1 –						
47											
48											
48											
50											
51											
52											
53											
54											
55											
56											
57											
58											
59											
60											
61											
62											
63											
64											
65											
66											
67											
68											
69											
70											
71											
72											
73					4						
74											
75											

	U	V	W	Х	ΥZ	AA	AB	AC	AD	AE
38										
38 39										
40							2			
41										
42										
43										
44										
44 45										
46 47										
47										
48										
49										
50		7								
51										
51 52										
53										
53										
54 55										
56										
57 58 59										
58										
59										
60										
61							Ī-			
62										
63										
64 65										
65										
66										
67										
68										
69										
70										
71 72 73										
72										
73									,	
74 75							,-			
75										

	AF	AG	АН	AI	AJ	AK	AL	AM	AN
38									
38 39									
40									
41									
42						1			
42 43									
44 45 46 47									
45									
46									
47									
48									
49									
48 49 50 51									
51									
52									
53			,						
54									
54 55 56									
56									
57									
58									
59									
57 58 59 60									
61									
62									
63									
63 64 65 66 67									
65									
66									
67									
68									
69									
70									
71									
69 70 71 72 73 74 75									
73									
74									
75									

	AO	AP	AQ	AR	AS	AT	AU	AV	AW	AX	AY	AZ
38												
38 39							1					
40 41 42												
41												
42							4					
43												
44									E			
44 45 46 47 48									341			
46							1					
47												
48												
49												
49 50 51 52 53 54 55												
51												
52												
53												
54												
55												
56												
57 58 59 60												
58												
59												
60												
61												
61 62 63												
63												
64 65 66 67												
65												
66												
67												
68												
69												
70												
71					2 0.0		12 20			1.0		
71 72 73 74 75												
73												
74												
75												

	BA
38	
39	
40	
41	
42	
43	
44	
45	
46	
47	A T
48	
49	
50	
51	
52	
53	
54	
55	
56	
57	
58	
59	
60	
61	
62	
63	
64	
65	
66	
67	
68	
69	
70	
71	11
72	
73	
74	
75	

Α	В	С	D	Е	F	G	Н
76		Avg. Number of Events/hr				Ldn:	6.4 dBA
77						Incremental Ldn (Src 1-4):	64.4 dBA
78	Nighttime hrs	Avg. Number of Locos/train					
79		Speed (mph)					
30		Avg. Number of Events/hr					
31							
32	Distance	From Source to Receiver (ft)					
33	Adjustments						7
34							
35							
36							
37							
38							
39							
90							
91							
92							
93							
94							
95							
96							
97							
98							
99							
00							
01							
02							
03							
04							
							1
.05							
06							Į.
.07							
.08							
.09							
10							
11							
12							
13							

76 6 77 78 8 9		I	J	К	L	М	N	0	Р	Q	R	S	Т
78 60 61 61 61 61 61 61 61 62 61 62 63 64<	76												
78 60 61 61 61 61 61 61 61 62 61 62 63 64<	77												
79	78									1			
80 60<	79												
81 6 7 6 7 6	80												
83 64 68<	81												
83 64 68<	82												
85 6 6 6 6 6 6 6 6 6 6 6 6 7 6 6 6 7	83												
85 6 6 6 6 6 6 6 6 6 6 6 6 7 6 6 6 7	84												
87 88 60<	85												
88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 111	86												
88 60<	87												
88 60<	88												
91 92 93 94 95 96 96 97 97 98 99 99 99 99 90 90 90 90 90 90 90 90 90	89												
92 93 94 94 95 96 97 98 99 99 99 90 90 90 90	90												
92 93 94 94 95 96 97 98 99 99 99 90 90 90 90	91												
94 95 96 97 98 99 <td< td=""><td>92</td><td></td><td></td><td></td><td></td><td></td><td>1 2</td><td></td><td></td><td></td><td></td><td></td><td></td></td<>	92						1 2						
94 95 96 97 98 99 <td< td=""><td>93</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>	93												
95 96 97 98 99 <td< td=""><td>94</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>	94												
96 97 98 99<	95												
98 99 <td< td=""><td>96</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>	96												
99 99 99 99 99 99 99 99 99 99 99 99 99 99 90 <td< td=""><td>97</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>	97												
100 101 102 103 104 105 106 107 108 108 108 109 1	98												
100 101 102 103 104 105 106 107 108 108 108 109 1	99												
101 102 103 104 105 105 106 107 108 108 109 1													
102 6 6 6 6 6 6 6 6 6 6 6 6 6 6 7	101												
104 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 7	102												
104 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 7	103												
105 106 107 108 109 110 111 111	104												
106 107 108 108 109 110 111 1	105												
107 108 109 110 111	106												
108 109 110 111	107												
110 111	108												
110 111	109												
111	110												
112	111												
	112												
	113												

	U	V	W	Х	ΥZ	AA	AB	AC	AD	AE
76										
76 77										
78 79										
80										
81										
81 82										
83										
84										
85										
86										
87							00			
88										
89										
90										
91										
92										
93										
94										
95										
96										
96 97										
98										
99										
100										
101										
102										
103										
104										
105										
106										
107										
107										
108 109										
109										
110										
111										
112 113										
113										

	AF	AG	AH	AI	AJ	AK	AL	AM	AN
76									
76 77									
78									
79									
80									
81									
82									
83									
84									
85									
86									
87									
88									
89									
90									
91						14			
92									
92 93									
94									
95									
96 97									
97									
98			7						
99									
100									
101									
102									
103									
104									
105								1	
106									
107									
108									
108 109									
110									
111									
112									
112 113									

	AO	AP	AQ	AR	AS	AT	AU	AV	AW	AX	AY	AZ
76 77												
77												
78									ET TI			
78 79 80 81												
80												
81												
82												
83												
84 85 86												
85												
86												
87												
88												
89												
90												
91 92 93							14					
92												
93												
94 95 96 97												
95												
96												
97												
98												
99												
100												
101												
102												
100 101 102 103												
104												
104 105 106 107 108 109												
106												
107												
108												
109												
110												
111												
112												
112 113												

	ВА
76	
77	
78	
79	
80	
81	
82	
83	
84	
85	
86	
87	
88	
89	
90	
91	1
92	
93	
94	
95	
96	
97	
98	
99	
100	
101	
102	
103	
104	
105	
106	
107	
108	
109	
110	
111	
112	
113	

Α	В	С	D	Е	F	G	Н
114							
115							
116							
117							
118							
119							
120							
121							
122							
123							
124							
125							
126							
127							
128							
129							
130							
131	1-						
132							
133							
134	1						
135	1						
136							
137	1						
138							
139	1						
140							
141	1						
142	1						
143							
144	4						
145	1-2						
146							
147							
148	}						
114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152	1						
150							
151							
152							

	I	J	K	L	M	N	0	Р	Q	R	S	Т
114												
115												
116												
117												
118												
119												
115 116 117 118 119 120												
121												
122												
123												
124												
125												
126												
127												
128												
129												
130												
131												
132					<u> </u>							
133												
134												
135												
136												
137												
138												
139												
140												
141												
142												
143					j.							
144												
145												
146												
147												
148												
149												
150												
121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 150												
152												

	U	V	W	ΧY	Z	AA	AB	AC	AD	AE
114										
115										
116										
117										
118										
119										
120										
121										
122										
123										
124										
125										
126										
115 116 117 118 119 120 121 122 123 124 125 126 127 128 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 149										
128										
129										
130										
131										
132										
133										
134										
135										
136										
137										
138										
139										
140										
141										
142										
143										
144										
145										
146										
147										
148										
149										
150										
150 151 152										
152										

	AF	AG	АН	AI	AJ	AK	AL	AM	AN
114									
115 116									
116									
117									
118									
119									
117 118 119 120									
121									
122									
123									
124									
125									
121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147									
127									
128									
129									
130									
131									
132									
133									
134									
135									
136									
137									
138									
139									
140									
141							J=		
142				_					
143							7:		
144							-		
145							/=		
146							J		
147							J		
148							J		
149							7		
150							J		
149 150 151 152							7		
152									

	AO	AP	AQ	AR	AS	AT	AU	AV	AW	AX	AY	AZ
114												
115												
116												
117												
118				1								
119												
120							1					
121												
122				m n			12.5					
123				1								
124												
125												
114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 152												
127				ė –							,e	
128												
129	- 1											
130												
131	- 1											
132												
133												
134												
135	[
136												
137												
138												
139	1											
140												
141	- 1											
142							11-11-11					
143												
144							1					
145												
146							h					
147												
148							h					
149												
150												
151												
152												

	BA
114	
115	
116	
117	
118	
119	
120	
121	
122	
123	
124	
125	
126	
127	
128	
129	
130	
131	
132	
133	
134	
135	
136	
137	14
138	
139	
140	
141	
142	
143	
144	
145	
146	
147	
148	
149	
150	
151	
152	

Cell: D11

Comment:

Cell: D12

Comment:

Cell: D13

Comment:

Cell: H15

Comment:

Cell: H16

Comment:

Cell: D18

Comment:

Cell: D21

Comment:

Cell: D22

Comment:

Cell: D32

Comment:

Cell: D38

Comment:

Cell: D39

Comment:

Cell: D49

Comment:

Cell: D55

Comment:

Cell: D56

Comment:

Cell: D66

Comment:

Cell: D72

Comment:

Cell: D73

Comment:

Cell: D83

Comment:

Cell: D89

Comment:

Cell: D90

Comment:

Cell: D100

Comment:

Cell: D106

Comment:


Cell: D107

Comment:


Cell: D117

Comment:

	Α	В	С	D	E	F	G	Н	I
1									
2									
3					- = 1				
4									
5									
6									
7			Project:	FTA Example	5-1, Part 1				
8			Receiver:						
9									
10							Noise C	riteria	
11			Source	Distance	Project Ldn	Existing Ldn	Mod. Impact	Sev. Impact	Impact?
12		1	Diesel Electric Locomotive	50 ft	63.8 dBA	60 dBA	58 dBA	63 dBA	Severe Impact
13		2	Rail Car	50 ft	55.6 dBA	60 dBA	58 dBA	63 dBA	None
14		3	Layover Tracks (commuter r	ft	6.4 dBA	60 dBA	58 dBA	63 dBA	None
15			Diesel Electric Locomotive	ft	6.4 dBA	60 dBA	58 dBA	63 dBA	None
16		5		ft		60 dBA	58 dBA	63 dBA	
17		6		ft		60 dBA	58 dBA	63 dBA	
18			Combined Sources		64 dBA	60 dBA	58 dBA	63 dBA	Severe Impact



	М	N
1		
2		
3		
4		
2 3 4 5 6		-
6		
7		
8		
9		
10		
11		
12		
13		(<u></u>
14		_
15		
16		
17		_
18	rate Impact	
19		
20	re Impact	
21	iver 1	-
	iveri	-
23 24		
25		-
26	- 40	-
27		+
28		-
29		+
30		-
31		-
32		
33		-
34		
35		-
36		-
37		-
38		
39		
40		
41		4
42		
43		
44		



	M	N
45		
46		
47		
48		_
49		
50		
51		
52 53 54		
53	rate Impact	
54		
55 56	e Impact	
56	ver 1	
57	Veri	
58		
59		
60		
61		
62		
63		
64		8
65		
66		
67		
68		